

LAUGFS

DUAL ASSEMBLY

READY FOR ANYTHING



DUAL ASSEMBLY TYRES (Solid twin wheels) are specially designed for excavators running on waste and recycling locations. The assembly consists of a pair of tyres mounted on rims with a spacer in between to avoid any dual touching. This twin assembly provides superior tyre life as well as resistance against damages and punctures.





DUAL ASSEMBLY OPTIMA



DUAL ASSEMBLY STD

- Innovative tread design - offers excellent traction
- Reinforced sidewall protection - eliminates punctures
- Large contact area - reduces tyre stress and uneven wear for maximum durability

RESILIENT TYRES - DUAL ASSEMBLY - STANDARD

Tyre Size	Rim Size	EASY FIT /Normal	Tread Pattern {Smooth (SM) / Traction (TR) / Rib (R.)}	Tyre Dimension				Load Capacity (kg)					Finished tyre weight(kg)	Pcs/20ft	
				Inch		mm		Counter balanced lift Trucks		Other Vehicles (Trailers)					Static
				Max Width	O.D.+/- 2%	Max Width	O.D.+/- 2%	Load Wheels	Steering Wheels	Up to 6Km/h	Up to 10Km/h	Up to 25Km/h			
															up to 25Km/h
9.00-20	7.00-20	N	TR	9.0	39.0	229	990	5400	4500	5400	4905	4500	6795	123.00	100
10.00 - 20	7.00 - 20	N	TR	9.9	41.1	251	1045	6000	5000	6000	5450	5000	7550	173.20	90
10.00 - 20	7.50 - 20	EF/N	TR	9.9	41.1	251	1045	6000	5000	6000	5450	5000	7550	175.60	90
10.00 - 20	8.00-20	N	TR	9.9	41.1	251	1045	6000	5000	6000	5450	5000	7550	177.80	90
11.00 - 20	7.00 - 20	N	TR	9.9	41.1	251	1045	6000	5000	6000	5450	5000	7550	173.20	90
11.00-20	7.50 - 20	EF/N	TR	9.9	41.1	251	1045	6000	5000	6000	5450	5000	7550	175.60	90
11.00 - 20	8.00-20	N	TR	9.9	41.1	251	1045	6000	5000	6000	5450	5000	7550	177.80	90
12.00 - 20	8.0 - 20	N	TR	11.2	43.2	285	1098	7500	6300	7560	6885	6300	9515	211.00	70
12.00 - 20	8.5 - 20	N	TR	11.2	43.2	285	1098	7500	6300	7500	6885	6300	9515	212.00	70

RESILIENT TYRES - DUAL ASSEMBLY- OPTIMA

Tyre Size	Rim Size	EASY FIT /Normal	Tread Pattern {Smooth (SM) / Traction (TR) / Rib (R.)}	Tyre Dimension				Load Capacity (kg)					Finished tyre weight(kg)	Pcs/20ft	
				Inch		mm		Counter balanced lift Trucks		Other Vehicles (Trailers)					Static
				Max Width	O.D.+/- 2%	Max Width	O.D.+/- 2%	Load Wheels	Steering Wheels	Up to 6Km/h	Up to 10Km/h	Up to 25Km/h			
															up to 25Km/h
10.00 - 20	7.50 - 20	EF/N	TR	9.8	40.8	248	1036	6000	5000	6000	5450	5000	7550	151.7	90
10.00 - 20	8.00 - 20	EF/N	TR	9.8	40.8	248	1036	6000	5000	6000	5450	5000	7550	152.7	90



LAUGFS Corporation (Rubber) Limited,
 No.101, Maya Avenue, Colombo 6, Sri Lanka.
 Tel: +9411 5 566 222 | e mail: info.rubber@laugfs.lk
 Web: www.laugfsindustrialtyres.lk | www.laugfs.lk