

LAUGFS SKS TYRES



SKS - LAUGFS (SOLID GRIP) TYRES are designed for the use of heavy duty applications. Its wide lug tread pattern and aperture side walls promote a maximum tyre life and outstanding performance.



LAUGFS
INDUSTRIAL TYRES



SKS

- Extra wide deep lug design - Longest wear and excellent traction in off road conditions
- Ride comfort - Aperture wall designed for shock absorption
- Hauler stepped tread design - Provides excellent clean out for improved off-road traction
- Fea-validated aperture design - Improves ride quality and reduces cracking

SOLID GRIP												
Tyre Size	Rim Size	EASY FIT /Normal	Tread Pattern {Smooth (SM) / Traction (TR) / Rib (R.)} (APP - Aperture) (ND- Non Directional	Tyre Dimension				Load Capacity (kg)			Finished tyre weight(kg)	Pcs/20ft
				Inch		mm		Other Vehicles (Trailers)				
				Max Width	O.D.+/-2%	Max Width	O.D.+/-2%	Up to 6Km/h	Up to 10Km/h	Up to 25Km/h		
110/75-6	3.00-6	N	RIB LUG	4.3	12,2	108	311				5.9	
5.70-12	4.00-12	N	SKS -APP	5.7	22	144	560	1755	1595	1352	22	600
30x10-16	6.00G-16	N	SKS -APP 2A	9.1	29.4	233	746	3300	3006	2525	66.3	210
31x10-20	7.50-20	EF/N	SKS -APP	9.4	30.9	238.5	785	3600	3273	2975	63	120
31x10-20	7.50-20	EF/N	SKS	9.4	30.9	238.5	785	4235	3850	3500	64	120
33x12-20	7.50-20	EF/N	SKS	11.3	32.9	288	837	5920	5390	4900	91.5	110
33x12-20	8.00-20	EF/N	SKS	11.3	32.9	288	837	5920	5390	4900	92.9	110
33x12-20	7.50-20	EF/N	SKS- APP	11.3	32.9	288	837	5032	4582	4165	90.5	110
33x12-20	8.00-20	EF/N	SKS- APP	11.3	32.9	288	837	5032	4582	4165	91.5	110
33x12-20	7.50-20	EF/N	SKS- APP 2A	11.3	32.9	288	837	4529	4124	3749	89	110
33x12-20	8.00-20	EF/N	SKS- APP 2A	11.3	32.9	288	837	4529	4124	3749	91.2	110
33x12-20	7.50-20	EF/N	SM	11.3	32.9	288	837	5920	5390	4900	102.2	110
33x12-20	8.00-20	EF/N	SM	11.3	32.9	288	837	5920	5390	4900	103.2	110
33x12-20	7.50-20	EF/N	SM-APP	11.3	32.9	288	837	5032	4582	4165	100.5	110
33x12-20	8.00-20	EF/N	SM-APP	11.3	32.9	288	837	5032	4582	4165	101.5	110
33x12-20	7.50-20	EF/N	SM-APP 2A	11.3	32.9	288	837	4529	4124	3749	99.6	110
33x12-20	8.00-20	EF/N	SM-APP 2A	11.3	32.9	288	837	4529	4124	3749	100.6	110
34x10-20	7.50 - 20	EF/N	ND-SKS-APP 1A	9.9	33.7	252	855	5032	4582	4165	92.8	108
36x12-20	7.50 - 20	N	SKS -APP 2FA	12.0	36.2	305	919	4800	4400	4000	120.5	84
36x12-20	8.00-20	N	SKS -APP 2FA	12.0	36.2	305	919	4800	4400	4000	122	84
13.00-24	8.5-24	N	SKS- APP 2A	12.8	50.4	325	1280	7700	7000	6350	287	49
14.00-24	8.5-24	N	SKS- APP 2A	13.9	52.4	352	1332	11100	10100	9300	325	30